









BOD8902 **Συλλέκτης λαδιού αέρος**



Στοιχεία Προϊόντων

- Αποστραγγίζει και μέσω της βαρύτητας, αλλά και μέσω του αποδοτικού μηχανισμού αναρρόφησης
- Περιλαμβάνει μια ευρεία συλλογή διαφορετικών καθετήρων, κατάλληλων για μια ποικιλία οχημάτων. Π.χ., ο χάλκινος καθετήρας χρησιμοποιείται για λάδι υψηλής θερμοκρασίας
- Flexible nylon: 5 x 700 mm, 6 x 700 mm, 7 x 1000 mm, 8 x 700 mm
- Rigid copper: 5 x 700 mm, 6 x 700 m
- Adaptors: for BMW diam:12,2mm and VAG Group diam:10mm
- Suction speed: 1,5 to 2 liters per minute with oil at 70°-80°C with 6mm probe and 8 bars/115 PSI air pressure
- Suction air pressure: 7-8 bars/100-115psi
- Maxi draining pressure: 1bar/14.5psi
- Maxi draining and suction tank capacity: 70L
- Reinforced connection between tank and oil tube to minimize the risk of leakages
- Swiveable offset designed funnel ensures a high flexibility and 18 liters capacity
- Metal reinforced hoses for improved durability
- Foam protected handle for insulation and to avoid scratches on vehicles in case of an accident
- Cooper muffler for increased tool life
- Gauges indicating the level of contained liquid, air tank and the suction pressures
- Useful plastic tray for screws, tools and others equipment
- Certified according to 2006/42/EC + BS EN1494
- Option: 60 cm extension funnel easy to position & capture fluid ref. BOD8901AC1
- Option: 60 cm extension funnel easy to position & capture fluid ref. BOD8901AC1

Ιδιότητες Προϊόντων

Προϊόν						
BOD8902	90 l	1100-1700 mm	632 mm	413 mm	1000 mm	38 kg

Follow the Fish!

