



BBRBB12 12V Electrical Brake Bleeder



PRODUCT DETAILS

- Selectable pulse and continuous bleeding modes to suit the requirements of all car manufacturers
- Suitable for DOT3, DOT4 and DOT5.1 brake fluids
- One-person operation machine: It gives more efficiency in the workshop
- Connection on vehicle's 12V battery
- Permissible pressure from 0.2 bar to 3.5 bar for both bleeding modes
- Pressure easily adjustable with the potentiometer
- Heavy duty bleeding pump
- Safety features
- Buzzer for reverse polarity connection and low brake fluid level
- The internal movable switch will never allow air to penetrate into the device and therefore into the vehicle brake system
- 6A fuse protects the main switches, pump and device electronics
- Stainless steel body protects against corrosive workshop fluids
- Quick connections with anti-return system
- 4.6 metre cable with insulated clamps of 20 mm opening width
- Supplied with an E20PW adaptor and a 1 litre bottle for used fluid
- 10 litre tank for fresh brake fluid with a sight gauge for brake fluid level in the tank
- Optimal operating temperature: $10^{\circ}\text{C} < T < 30^{\circ}\text{C}$
- CE certified and marked with individual serial number

PRODUCT ATTRIBUTES

Product					BAR		
BBRBB12	895 x 390 x 395 mm	12 V	4600 mm	X	0.2-3.5 bar	6 A	14.6 kg

Follow the Fish!

