



**70S/H**  
**Bit. Sextavado**



DETALHES DO PRODUTO

- Encaixe: 5/16" DIN 3126-C 8, ISO 1173
- Acabamento: fosfato de zinco
- Material: liga de aço de alto desempenho



## ATRIBUTOS DO PRODUTO

Produto				
<b>70S/H4-2P</b>	2	4 mm	30 mm	24 g
<b>70S/H4-5P</b>	5	4 mm	30	60 g
<b>70S/H5-5P</b>	5	5	30	66 g
<b>70S/H5-2P</b>	2	5 mm	30 mm	26 g
<b>70S/H6-5P</b>	5	6	30	71 g
<b>70S/H6-2P</b>	2	6 mm	30 mm	28 g
<b>70S/H7-2P</b>	2	7 mm	30 mm	30 g
<b>70S/H7</b>	5	7 mm	30 mm	75 g
<b>70S/H8-2P</b>	2	8 mm	30 mm	31 g
<b>70S/H10-2P</b>	2	10 mm	30 mm	40 g
<b>70S/H10</b>	5	10 mm	30 mm	101 g
<b>70S/H12-2P</b>	2	12 mm	30 mm	50 g
<b>70S/H12</b>	5	12 mm	30 mm	125 g
<b>70S/H14-2P</b>	2	14 mm	30 mm	60 g
<b>70S/H14</b>	5	14 mm	30 mm	151 g

