



74S/H
Bit. Sextavado







DETALHES DO PRODUTO

- Encaixe: 11,2 mm (7/16") DIN 3126-E11.2, ISO 1173
- Acabamento: fosfato de zinco
- Material: liga de aço de alto desempenho
- Suporte de bits: parafuso de fixação
- Adaptadores adequados: 7809H



ATRIBUTOS DO PRODUTO

Produto				
74S/H4-2P	2	4 mm	35 mm	46 g
74S/H4	5	4 mm	35 mm	115 g
74S/H5-2P	2	5 mm	35 mm	49 g
74S/H6-2P	2	6 mm	35 mm	49 g
74S/H6	5	6 mm	35 mm	124 g
74S/H7-2P	2	7 mm	35 mm	50 g
74S/H7	5	7 mm	35 mm	126 g
74S/H8-2P	2	8 mm	35 mm	51 g
74S/H8	5	8 mm	35 mm	127 g
74S/H10-2P	2	10 mm	35 mm	61 g
74S/H10	5	10 mm	35 mm	154 g
74S/H12-2P	2	12 mm	35 mm	72 g
74S/H12	5	12 mm	35 mm	181 g
74S/H14-2P	2	14 mm	35 mm	82 g
74S/H14	5	14 mm	35 mm	202 g
74S/H17-2P	2	17 mm	35 mm	98 g
74S/H17	5	17 mm	35 mm	244 g

Follow the Fish!

