



BBCE12-F100

100A Battery Charger/Power Supply



PRODUCT DETAILS

- 70 amp fully automatic battery charger/maintainer for 12V batteries
- Able to supply up to 70 amperes continuously, but can reach 100A for a period of 3 minutes
- It is also a power supply that maintains a stable voltage (allowing voltage adjustment between 13.0-14.8V) under varying loads, during major vehicle ECU reprogramming and diagnostic work
- Application: boats, passenger cars, campers, commercial vehicles, buses, agriculture vehicles, trucks, etc.
- Aided by microprocessor controlled technology
- This technology allows a multi-rate charging sequence for added precision, safety and increase battery life
- Designed for all types of lead-acid batteries such as AGM, Cal/Cal, Gel, VRLA, and Start&Stop batteries
- Charging mode can be set to Automatic or Manual mode, where you can set the charging rate to 4, 20 or 70 amps
- Manual mode allows the desired charging time to be set
- Desulphating mode, achieving 15.8V max
- Showroom (Supply) mode available
- Float-mode monitoring: Automatically maintains optimum battery charge
- Heavy duty construction
- Andersson connector that ensures an optimal connection and current transfer
- Heavy-duty clamps with replaceable jaws on a 5 metre cable, with 42 mm clamp opening width and equipped with a copper bridge between the clamp jaws to ensure even current distribution between the jaws
- Safe
- Reverse polarity protection
- Dual temperature-controlled cooling fans
- Adjustable mounting brackets for easy permanent installation on most shop post lifts
- Operating temperature: -20 °C / +40 °C
- Working life (MTBF): 85,000 hours
- Package contents: Charger/maintainer, clamps, power supply cable, 4 mounting brackets and screws, and user manual in 16 languages
- CE certified

Follow the Fish!



PRODUCT ATTRIBUTES

Product	V	A						IP		
BBCE12-F100	12 V	4/20/70/100A A	X	0 - 2000 A·h	5000 mm	X	42 mm	20	450 x 140 x 450 mm	9820 g

Follow the Fish!



Contact: info@bahco.com / www.bahco.com