




3802

Makina testere lamaları.



ÜRÜN DETAYLARI

- Hemen hemen her türlü malzemenin kesimine uygundur
- Yüksek hız çelik testere laması
- Yüksek kontrollü, modern makinalara uygundur



Follow the Fish!



ÜRÜN ÖZELLİKLERİ

Ürün		L	W	T	
3802-300-25-1.25-6	6	300 mm	25 mm	1.25 mm	73 g
3802-300-25-1.25-10	10	300 mm	25 mm	1.25 mm	73 g
3802-300-25-1.25-14	14	300 mm	25 mm	1.25 mm	73 g
3802-300-32-1.60-6	6	300 mm	32 mm	1.60 mm	120 g
3802-300-32-1.60-10	10	300 mm	32 mm	1.60 mm	120 g
3802-350-25-1.25-6	6	350 mm	25 mm	1.25 mm	88 g
3802-350-25-1.25-10	10	350 mm	25 mm	1.25 mm	88 g
3802-350-25-1.25-14	14	350 mm	25 mm	1.25 mm	88 g
3802-350-32-1.60-4	4	350 mm	32 mm	1.60 mm	145 g
3802-350-32-1.60-6	6	350 mm	32 mm	1.60 mm	145 g
3802-350-32-1.60-8	8	350 mm	32 mm	1.60 mm	145 g
3802-350-32-1.60-10	10	350 mm	32 mm	1.60 mm	145 g
3802-350-32-1.60-14	14	350 mm	32 mm	1.60 mm	145 g
3802-400-25-1.25-6	6	400 mm	25 mm	1.25 mm	98 g
3802-400-25-1.25-10	10	400 mm	25 mm	1.25 mm	98 g
3802-400-25-1.25-14	14	400 mm	25 mm	1.25 mm	98 g
3802-400-32-1.60-4	4	400 mm	32 mm	1.60 mm	160 g
3802-400-32-1.60-6	6	400 mm	32 mm	1.60 mm	160 g
3802-400-32-1.60-8	8	400 mm	32 mm	1.60 mm	160 g
3802-400-32-1.60-10	10	400 mm	32 mm	1.60 mm	160 g
3802-400-32-1.60-14	14	400 mm	32 mm	1.60 mm	160 g
3802-400-38-2.00-4	4	400 mm	38 mm	2.00 mm	219 g
3802-400-38-2.00-6	6	400 mm	38 mm	2.00 mm	219 g
3802-400-38-2.00-10	10	400 mm	38 mm	2.00 mm	219 g
3802-425-32-1.60-6	6	425 mm	32 mm	1.60 mm	170 g
3802-425-32-1.60-10	10	425 mm	32 mm	1.60 mm	170 g
3802-450-32-1.60-4	4	450 mm	32 mm	1.60 mm	177 g
3802-450-32-1.60-6	6	450 mm	32 mm	1.60 mm	177 g
3802-450-32-1.60-10	10	450 mm	32 mm	1.60 mm	177 g
3802-450-32-1.60-14	14	450 mm	32 mm	1.60 mm	177 g
3802-450-38-2.00-4	4	450 mm	38 mm	2.00 mm	249 g
3802-450-38-2.00-6	6	450 mm	38 mm	2.00 mm	249 g
3802-450-38-2.00-8	8	450 mm	38 mm	2.00 mm	249 g
3802-450-38-2.00-10	10	450 mm	38 mm	2.00 mm	249 g
3802-475-38-2.00-8	8	475 mm	38 mm	2.00 mm	279 g
3802-500-38-2.00-4	4	500 mm	38 mm	2.00 mm	304 g
3802-500-38-2.00-6	6	500 mm	38 mm	2.00 mm	304 g
3802-500-38-2.00-8	8	500 mm	38 mm	2.00 mm	304 g
3802-500-38-2.00-10	10	500 mm	38 mm	2.00 mm	304 g
3802-500-45-2.25-10	10	500 mm	45 mm	2.25 mm	398 g
3802-500-50-2.50-4	4	500 mm	50 mm	2.50 mm	513 g
3802-500-50-2.50-6	6	500 mm	50 mm	2.50 mm	513 g
3802-525-38-2.00-6	6	525 mm	38 mm	2.00 mm	314 g
3802-525-38-2.00-8	8	525 mm	38 mm	2.00 mm	314 g
3802-525-38-2.00-10	10	525 mm	38 mm	2.00 mm	314 g
3802-550-38-2.00-6	6	550 mm	38 mm	2.00 mm	329 g
3802-550-50-2.50-4	4	550 mm	50 mm	2.50 mm	553 g
3802-550-50-2.50-6	6	550 mm	50 mm	2.50 mm	553 g
3802-550-50-2.50-8	8	550 mm	50 mm	2.50 mm	553 g
3802-550-50-2.50-10	10	550 mm	50 mm	2.50 mm	553 g
3802-575-50-2.50-4	4	575 mm	50 mm	2.50 mm	568 g
3802-575-50-2.50-6	6	575 mm	50 mm	2.50 mm	568 g
3802-600-50-2.50-4	4	600 mm	50 mm	2.50 mm	588 g
3802-600-50-2.50-6	6	600 mm	50 mm	2.50 mm	588 g
3802-600-50-2.50-8	8	600 mm	50 mm	2.50 mm	588 g
3802-650-50-2.50-4	4	650 mm	50 mm	2.50 mm	634 g
3802-650-50-2.50-6	6	650 mm	50 mm	2.50 mm	634 g
3802-700-50-2.50-3	3	700 mm	50 mm	2.50 mm	679 g
3802-700-50-2.50-4	4	700 mm	50 mm	2.50 mm	679 g
3802-700-50-2.50-6	6	700 mm	50 mm	2.50 mm	679 g
3802-750-50-2.50-4	4	750 mm	50 mm	2.50 mm	730 g
3802-750-50-2.50-6	6	750 mm	50 mm	2.50 mm	730 g

Follow the Fish!



Contact: info@bahco.com / www.bahco.com